

## PINGU 140



### Characteristics

|   |  |
|---|--|
| Structure   | White version or Stainless steel 18/10 int.+ext.   |
| Insulation thickness  | 40 (polyur. mm)  |
| Doors number  | 1  |
| Door type   | Glass  |
| Refrigeration type  | Ventilated   |
| Refrigerant type  | R404A  |
| Temperature range   | +4°  |
| Temperature control/<br>adjustment  | Control:<br>Door alarm, Temperature alarm, Dirty<br>Condenser alarm, faulty condenser, Faulty<br>evaporator, faulty sensor, RS485 In/Out,<br>Memory of last 12 alarms  |
| Defrosting type   | Auto   |
| Voltage   | 230V/1/50Hz  |
| Castors   | Standard fitted  |
| Capacity (LT)   | 140  |
| Safety key locking  | Standard fitted  |
| Internal lighting   | Standard fitted  |
| Digital monitor<br>(Alarm system)   | Standard fitted:<br>- Back up battery (in case of power failure)<br>- Temperature tracking with SD card incl.<br>download interf. SW (memory of all temp<br>Values and operation data, min 5 years)<br>- 2 output relays (dry contact) |
| Drawers nr.   | 3  |
| Storage capacity<br>(blood bags nr., 450 ml)  | 63   |
| Dimensions (cm)   | 52 x 64 x 100  |
| Net weight (kg)   | 73   |
| Automatic water evaporation.<br>Probe for product simulation.<br>Ext. terminal board for RS485/dry contacts.<br>Available also with fully insulated door. |  |
| Equipment in accordance with Directive 93/42/EEC annex V,<br>article 3 and following modifications.   |  |

### Accessories

- Printer
- Drawer perspex front (H=83 mm)
- Pt100 probe
- WEB LIGHT SERVER (Ethernet + GSM)
- Remote panel
- GSM Communicator CF2008 module
- PT100 Extension module + nr.1 PT100 probe + 4-20mA output
- Frequency 60Hz
- Voltage 115V