

PINGU 400



Characteristics

Structure	White version or Stainless steel 18/10 int.+ext.
Insulation thickness	50 (polyur. mm)
Doors number	1
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+4°
Temperature control/ adjustment	Control: Door alarm, Temperature alarm, Dirty Condenser alarm, faulty condenser, Faulty evaporator, faulty sensor, RS485 In/Out, Memory of last 12 alarms
Defrosting type	Auto
Voltage	230V/1/50Hz
Castors	Standard fitted
Capacity (LT)	400
Safety key locking	Standard fitted
Internal lighting	Standard fitted
Digital monitor (Alarm system)	Standard fitted: - Back up battery (in case of power failure) - Temperature tracking with SD card incl. download interf. SW (memory of all temp Values and operation data, min 5 years) - 2 output relays (dry contact)
Drawers nr.	6
Storage capacity (blood bags nr., 450 ml)	180
Dimensions (cm)	60 x 66 x 196
Net weight (kg)	150

Automatic water evaporation.

Probe for product simulation.

Ext. terminal board for RS485/dry contacts.

Available also with fully insulated door.

Equipment in accordance with Directive 93/42/EEC annex V,
article 3 and following modifications.

Accessories

- Printer
- Drawer perspex front (H=83 mm)
- Remote panel
- PT100 probe
- WEB LIGHT SERVER (Ethernet + GSM)
- GSM Communicator CF2008 module
- Pt100 Extension module + nr.1 PT100 probe + 4-20mA output
- Frequency 60Hz
- Voltage 115V